Date: _____ PRO-code: _____ Hour meter: _____

Lift S/N: _____ In-Service Date: _____Technician: _____

Manager's signature is required on the bottom of this form if technician finds that Level 2 or 3 service is needed on the lift.

| CHECK OFF | ORDER | Podzilla Full PM Service - Every 100 Hours of Runtime |
|---|---|---|
| | 1 | Remove air filter and clean or replace as needed. |
| | 2 | Change fuel filter. |
| | 3 | Change oil filter. |
| | 4 | Change engine oil. |
| | 5 | Change spark plugs. |
| | 6 | Change hydraulic filter. |
| | 7 | Check hydraulic fluid level. Correct level is 3/4 -ull in sight glass. Use only Chevron Clarity ISO-32. |
| | 8 | Check water level in battery. If low, refill to bottom edge of plastic. |
| | 9 | Use air impact on drive and steer tire lug nuts to ensure tightness. |
| | 10 | Grease all drive and caster bearings. |
| | 11 | Grease all inner steel tubes. |
| | 12 | Inspect frame and weld joints for damage or cracks--report damage findings. |
| | 13 | Inspect lift chain assemblies for excessive wear and cotter pins for correct placement. |
| | 14 | Inspect slider eyelet assemblies for excessive wear. |
| | 15 | Inspect tires for excessive rim or tire damage--per standard. |
| | 16 | Inspect tire pressure and follow manufacturer's recommended PSI--printed on tire. |
| | 17 | Inspect ram assemblies for signs of leaks--report leaks to management. |
| | 18 | Inspect wear disk cap plate bolts and hardware. |
| | 19 | Pressure wash lift as necessary to project a favorable image on the PODS brand. |

Technician's Comments:

If checked, needs higher-level service ☐

Manager's signature: _____